

FRAMED SLIDING PANEL

IDEAL 38



Introducing the IDEAL 38

The IDEAL 38 is a sliding panel system manufactured from aluminium profiles that are not thermally insulated. The easy to operate system is particularly suitable for large-scale applications.

Individual needs are covered with the IDEAL 38:

- Select your design: 1, 2, 3 or 4 rails
- Adjustable glass thicknesses: single-pane or double glazing up to 20 mm
- Individual colours: 28 standard colours at no extra cost



All elements in this system are free sliding, with the element running inside equipped with a multiple seal and window handles, the outer with a recessed reversible handle.



The use of high-quality double rollers guarantees permanently smooth sliding even at element weights of up to 100 kg.

Common applications

The possible applications for the IDEAL 38 are extremely diverse. As a non-thermal system, it is particularly suitable for the following areas:

- Balcony glazing
- Sitting area glazing
- Integrated into patio roofing

5 features at a glance

- Non-thermal aluminium system
- Panel weight per element maximum 100 kg
- Panel width: up to a maximum of 2000 mm
- Panel height: up to a maximum of 2600 mm
- Element surface area: up to a maximum of 4m²



Flat wall connection profiles shape the flowing transition from the masonry to the actual sliding panel.



Additional visual advantages include the rounded external profile edges and the slender profiles between elements to improve visibility.

Opening variants:

